

AWM100 WATERGUARD ACRYLIC WATERPROOFING MEMBRANE

1 – DESCRIPTION

AWM100 Waterguard Acrylic Waterproofing Membrane is a one component, water based, acrylic copolymer based elastic waterproofing membrane.

2 – PROPERTIES

- Ready to use
- Can be easily applied with airless spray gun, roller or brush
- Low labor cost
- Does not contain solvent, can be diluted with water
- Water vapor permeable
- Resistant to UV
- Maintains elasticity even at low temperatures
- Over paintable
- High opacity
- Can be colored with water based color pastes
- Seamless application

3 – APPLICATION AREAS

Waterproofing of;

- Balconies, terraces and roofs
- Facades
- Wooden surfaces
- Asphalt and bitumen floorings
- Roofing details such as gutters, chimney edges etc.

4 – INSTRUCTIONS

Ensure that the surfaces to be waterproofed are clean, dry and free from grease. On porous surfaces such as concrete, cement and plaster a primer (mixture of 4-5 parts one part acrylic waterproofing membrane and 1-2 parts of water) can be applied. It is recommended to apply anti-corrosive primers for metal surfaces. Apply non-diluted Acrylic waterproofing membrane on the surface by using airless spray gun, roller or brush only in a single direction. Wait sufficient amount of time to allow the first layer to dry. Then apply next layer in the opposite direction. The optimum layer thickness is approx. 1 mm. Apply minimum 2 layers. It is recommended to use reinforcing textiles for connection lines or surfaces with cracks.

5- STORAGE AND SHELF LIFE

12 months if stored properly in its original package between +5 °C and 25 °C in a dry environment and protected from direct sunlight.

6- RESTRICTIONS

- It should not be applied in case of risk of rain or frost.
- Prevent applied waterproofing layer from rain or frost for at least 24 hours
- Not suitable for pressurized water
- Not recommended for pedestrian or vehicle traffic. In such a case, the surface of waterproofing layers should be covered with suitable elements such as tiles or protective surface covering materials.

7- SAFETY & DISPOSAL

Check MSDS guidelines for disposal and further information concerning safety.

8- TECHNICAL FEATURES

Chemical Basis	: Acrylic copolymer
Solid Content	: %70-80
Density	: 1,37 ± 0,03 g / ml
Consistency / Color	: Liquid / White
Viscosity	: 50.000 ±5000 (Spindle No:6, 12rpm, 20°C)
Dry Time for Next Layer Application	: 4-5 hours (23°C, %50 R.H.)
Service Time	: 48 hours (23°C, %50 R.H.)
Consumption	: Horizontally 1,0-1,5 kg/m ² , vertically 0,75 kg/m ²
Elongation at Break	: ≥ 600% (DIN 53504)
Tensile Strength	: >1 N/mm ² (DIN 53504)
Application Temperature	: +5°C ile +35°C
Ambient Temperature	: +5 °C ile +35°C

DISCLAIMER

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.