

WATERGUARD (COOL ROOF)

1 – DESCRIPTION

Waterguard is a one component, cold applied, water based, modified polyurethane dispersion based elastic waterproofing membrane.

2 – PROPERTIES

- Ready to use
- High elasticity
- High UV stability
- Can be easily applied with airless spray gun, roller or brush
- Low labor cost
- Does not contain solvent, can be diluted with water
- Water vapor permeable
- Maintains elasticity even at low temperatures
- Over paintable
- High opacity
- Seamless application
- High solar reflectance
- High resistance to dirt pick-up for long term solar reflectivity

3 – APPLICATION AREAS

- Waterproofing of exposed roofs in both new construction and refurbishment
- For reflective coating to enhance energy efficiency
- Suitable for metal, concrete, brick, stone, wood, asphalt and bitumen surfaces

4 – INSTRUCTIONS

- Ensure that the surfaces to be waterproofed are clean, dry and free from grease.
- Loose friable material must be completely removed from the surface by mechanical means
- Prior to application, mix Waterguard to achieve a homogeneous mixture
- Prior to waterproofing, detailing work should be completed. Waterproofing of details could be made by undiluted Waterguard. It is recommended to use reinforcing textiles for connection lines or surfaces with cracks.
- A primer (Waterguard diluted with 10-20% water mixture) can be applied before waterproofing.
- Once the primer becomes tack free apply Waterguard in 2-4 coats required by the system (Table 1,2,3)
- Clean all tools and application equipment with water immediately after use. Hardened / cured material can only be removed mechanically

Table 1: Waiting time after priming

Substrate Temperature	Relative Humidity	Waiting Time
+10 °C	50%	4-6 h
+20 °C	50%	2-4 h
+30 °C	50%	1-2 h

Table 2: Dry Time for Next Layer Application

Substrate Temperature	Relative Humidity	Waiting Time
+10 °C	50%	8-12 h
+20 °C	50%	6-8 h
+30 °C	50%	4-6 h

Table 3: Full cure times

Substrate Temperature	Relative Humidity	Full cure Time
+10 °C	50%	5-7 days
+20 °C	50%	4-6 days
+30 °C	50%	2-4 days

5- STORAGE AND SHELF LIFE

12 months if stored properly in its original package between +5 °C and 25 °C in a dry environment and protected from direct sunlight.

6- RESTRICTIONS

- It should not be applied in case of risk of rain or frost.
- Prevent applied waterproofing layer from rain or frost for at least 24 hours
- Not suitable for pressurized water
- Drying times provided are approximate values and could be affected by applied thickness, outside temperature and surface humidity. Low temperature and high humidity retard curing, while high temperatures and low humidity accelerate drying process.

7- SAFETY & DISPOSAL

Check MSDS guidelines for disposal and further information concerning safety.

8- TECHNICAL FEATURES

Chemical Basis	: Modified polyurethane dispersion	
Solid Content (by weight)	: 63-66%	
Density	: 1,35 ± 0,03 g / ml	
Consistency / Color	: Liquid / White	
PH	: 8-9	
Tensile Strength	: Approx. 1,5 N/mm ²	DIN 53504
Elongation at break	: Min. 150 %	DIN 53504
Viscosity	: 5000-15000 cp (20°C.S.No:05)	
Consumption	: 1,0-2,0 kg/m ² (primer+2 coats application)	
Reflectivity,%	: 85±0,5	
Application Temperature	: +5°C ile +35°C	
Ambient Temperature	: +5 °C ile +35°C	
Substrate Moisture Content	: < 6 %	

9- PACKAGING

Product Type	Volume
White (Plastic Pail)	5 kg, 20 kg

DISCLAIMER



The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.